ifoam PRO

Intelligent active foam generator

iFoam Pro provides everything you need to clean hoods, plenums, and exhaust system motors in a single unit.

- **Multijet system.** It automatically regulates all the parameters of the degreasing foam generation, guaranteeing perfect adherence of the chemical to any surface for effectively dissolving grease.
- **High pressure** water rinsing (150 bar)
- Power and speed for **cleaning large surfaces**.





Lance adjustable in angle
Easily reaches the most inaccessible spots.

LED indicator
Shows the status of the machine.



ECO mode.
Saves chemicals when cleaning less dirty surfaces.



rotojet
Rotating concentrated jet nozzle for high pressure, rinsing .Scrubs surfaces for more persistent grease.



Removable front panel for Chemical
Container system that guarantees a comfortable and safe handling.



THE EQUIPMENT INCLUDES



ADJUSTABLE LANCE.
Foam injection and high pressure rinsing

AC3303340 + AC3303344



HOSE.
High pressure liquid connection 26.24ft

AC3303222



ROTATING NOZZLE ROTOJET. High pressure rinsing

AC3303320

OPTIONAL ACCESORIES



HOSE REEL FOR MAINS WATER.
33 ft

HE7300200



UNIVERSAL TAP ADAPTER.

AC6200003



TAP CONNECTION FOR THREADED SOCKETS.

AC6200005

CONSUMABLES



COMEGRAS
Ultra-concentrated degreaser.
10 kg | 22 lb Jerrycan

PQ8100122

APPLICATIONS



Campana



Estractor

TECHNICAL FEATURES

Electric power supply	230V 50Hz	230V 60Hz	110V 60Hz
Water intake: Pressure Maximum temperature	Min. Pressure 2 bar Min. Pressure 29 psi 60ºC | 140 F		
High-pressure rinsing power	2350 W	1500 W	
Pump pressure high pressure	150 Bar 2175 psi	103 Bar 1500 psi	
Current consumption high pressure	10,7A	12,7A	
System power low pressure	340 W		
Pump pressure low pressure	8 Bar / 116 psi		
Current consumption low pressure	1,5A	3A	
Noise level	< 70 dB		
Control panel	Membrane keyboard		
Dimensions (L x W x H)	570 x 430 x 1040 mm 22.5 x 17 x 41 in		
Unloaded weight	55 kg | 121 lb		
Hose length	10 m 33 ft	8 m 26 ft	
Structure material	Stainless steel & HDPE		